## **Declaration of performance**

## Number: 2013-081 **Rijswaard facing brick**

## BENOR ) 😫 🕻 🧲

(4) Manufacturer:		
Steenfabriek De Rijswaard B.V. De Rijswaard 2 NL-5308 LV AALST	Tel: +31 (0)418 - 55 22 21 Fax: +31 (0)418 - 55 29 00 www.rijswaard.nl	RIJSWAARD° BAKSTEEN
(1) Unique identification code of the product- type	Rood	
(2) Typenumber	203822011 Redburn Multi Stock / DR12B	
(3) Intended use or uses of the construction productbouwproduct	U units for use in unprotected masonry walls, colums and partitions.	
(6) System or systems of assessment and verification of constancy of performance of the construction product	2+	
(7) Notified body	Notified Body KIWA 0620-CPD performed under system 2+ the initial inspection of the manufacturing plant and of the factory production control, performed the continuous surveillance, assessment and evaluation of the factory production control and issued the certificate of conformity of the factory production control.	

## (9) Declared performance: Dimensions English 213 Length mm Width 101 mm Height 64 mm Dimensional tolerance Т2 Range category **R1** U Flatness of bed faces NPD Metselbaksteen, **Categorie I** Parallellisme legvlakken NPD volgens EN77-1:2011 1550 kg/m3 Gross dry density + A1:2015 Net dry density NPD kg/m3 Tolerance Volumetric Mass: Class / % D1 | ±10 % Total volume frog <20% Group Eurocode 1 ≥ 15 Mean compressive strength N/mm2 ≥ 15 N/mm2 Normalised compressive strength Bond strength 0.15 - 0.30 50/50: 0.48 / 90/90: 0.52 EN 1745:2012 Thermal conductivity W/mK 5/10 Water vapour permeability [Durability : freeze/thaw resistance] F2 ≤ 15 % Water absorption m/md Initial rate of water absorption 1.5 - 4.0 kg/(m²min) **S**2 Active soluble salt content NPD [Dimensional stability: Moisture movement] mm/m Dangerous substances Voldoet NL-BBK A1 Reaction to fire

(10) The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4. Signed for and on behlaf of the manufacturer by

Atse Blei General Management

668

Aalst (NL) 30-Jan-2021